

CLB HYPER



Junta elástica integrada para el mejor acoplamiento de la bomba.



- Four pole (1450 RPM), air-cooled electric motor with thermal protection (three-phase models).
- Linear pump with three, ceramic-coated steel pistons and brass head with built-in bypass valve.
- Built-in elastic gasket to connect the pump (three-phase models).
- **Total stop delay and in low voltage.**
- Stainless steel suction and outlet valves.
- Integrated detergent suction with external suction probe.
- Pressure control valve.
- Glycerine pressure gauge.
- Steel frame.
- Steel covers.

- **3.700.0036** - Spray Gun M22-3/8" (1211LP)
- **3.700.0030** - M22-3/8" with quick coupling (1515LP/2015LP)



- **3.701.0015** - Lance M22 high/low pressure.



- **3.103.0050** - Nozzle type 0.45 (1211LP/2015LP)
- **3.103.0053** - Nozzle type 0.60 (1515LP)
- **3.103.0055** - Nozzle type 0.70 (2021LP)
- **3.103.0049** - Nozzle type 0.40 (2515LP)



- **4.618.0143** - High-pressure hose 10 m.



- Optional:**
- **6.608.0068**
Hose reel (hose not included)



CLB HYPER 2021LP

CLB HYPER 2515LP

Code	APLV86540113	8.654.0053
Pressure	200 bar	250 bar
Flow rate	1260 l/h	900 l/h
Input/voltage	9400 W-400 V~50 Hz 3 ph	8500 W-400 V ~ 50 Hz 3 ph
Motor-driven pump type/RPM	MPWJ5 / 1450 RPM	MPWJ5 / 1450 RPM
Max. water input temperature	40 °C	40 °C
Dimensions/weight	50x90x83/58 kg	50x90x83/59 kg